



PORTABLE DENSITY METER

DM-250.2

IN PROCESS TO EXCELLENCE

Specifications

Measuring range:	
Density	0... 3 g/cm ³ (0... 3000 kg/m ³)
Density Standard calibration	0.6... 1.2 g/cm ³ (600... 1200 kg/m ³)
	0.9... 1.8 g/cm ³ (900... 1800 kg/m ³)
Temperature	-40... +85°C (-40... +185°F)
Accuracy:	
Density	±0.0003 or ±0.0005 g/cm ³ (±0.3 or ±0.5 kg/m ³)
Temperature	±0.1°C (±0.2°F) or ±0.2°C (±0.4°F)
Repeatability:	
Density	±0.00015 or ±0.00025 g/cm ³ (±0.15 or ±0.25 kg/m ³)
Temperature	±0.1°C (±0.2°F)
Resolution:	
Density	0.0001 g/cm ³ (0.1 kg/m ³)
Temperature	0.01°C (0.02°F)
Supported measuring units	Real Density: g/cm ³ , kg/m ³ , lb/gal, lb/ft ³ ; API; SG Referred Density: at 15°C, 20°C, 60°F; API60; SG60 Tables ASTM D 1250 Alcohol Tables Temperature in °C or °F
Ambient temperature	-40... +85°C (-40... +185°F)
Depth of submersion	Up to 30 meters (100 ft.)
Sensor:	
Type	Vibrating element (Resonance principle)
Material	Stainless steel SS 316 L; NiSpan C; Hastelloy C22
Intrinsically safe:	
Controller	ATEX II (2G) EEx ib [ia] IIB T4
Level block with sensor	ATEX II 1G EEx ia IIB T4
Power supply	2 x NiMH 3.6V-1500 mAh
Operating time without charging	Appr. 12 hours
Dimensions, weight:	
Controller	180 x 80 x 40 mm (7.1 x 3.2 x 1.6"), 0.6 kg (1.3 lb)
Level block with sensor	420 x 245 x 140 mm (16.5 x 9.7 x 5.5"), 4 kg (8.8 lb)
Temperature compensation	Automatic
Viscosity compensation	Automatic
Data handling	Backlighted LCD display (2x16) Local memory up to 2000 results Build in Bluetooth for data transfer to printer or PC Optional Windows - based software

Advantages

- Direct density measurement
- Density Profile
- Temperature Profile
- Automatic temperature compensation
- No sampling required
- ATEX, IEC Hazloc certification
- Safe operation, low maintenance
- At any depths up to 30 meters
- Economical and easy to operate
- Measures highly viscous liquids up to 2000 cP
- Rigid construction for heavy duty outdoor operation
- Local results storage and Bluetooth data transfer

Applications


- Petroleum industry
- Ethanol production
- Food & Beverages
- Chemical industry
- Cosmetic industries
- Pharmaceutical industry

Delivered in compact carrying case



CASE

Able to download the measurements to PC;
Multifunctional software allows to proceed the
measurements results in user-convenient form;
Compatible for a Windows XP/Vista/7.



SOFTWARE

Immediate printout of the measurements;
No need for PC.



BLUETOOTH PRINTER

For more information please visit www.lemis-usa.com



LEMIS USA, Inc
15556 Summit Park Dr., Suite 601
Montgomery
TX 77356, USA
Ph.: +1 281 465 8441
E-mail: info@lemis-usa.com

